United States Patent [19]

Sasaki et al.

[11] Patent Number: 5,064,916 [45] Date of Patent: Nov. 12, 1991

[54]	ORGANOPOLYSILOXANE COMPOSITION FOR THE FORMATION OF A CURED RELEASE FILM	
[75]	Inventors:	Shosaku Sasaki, Ichihara; Hiroshi Masaoka, Saitama, both of Japan
[73]	Assignee:	Toray Silicone Company, Ltd., Tokyo, Japan
[21]	Appl. No.:	439,965
[22]	Filed:	Nov. 21, 1989
[30]	Foreign Application Priority Data	
Nov. 25, 1988 [JP] Japan 63-299301		
[51] Int. Cl. ⁵		
[58]		arch
[56] References Cited		
U.S. PATENT DOCUMENTS		
	4,256,870 3/1	981 Eckberg 528/15

 4,347,346
 8/1982
 Eckberg
 528/15

 4,609,574
 9/1986
 Keryk et al.
 427/407.1

 4,946,878
 8/1990
 Jensen et al.
 528/15

FOREIGN PATENT DOCUMENTS

1240520 7/1971 United Kingdom .

Primary Examiner—Melvyn I. Marquis Attorney, Agent, or Firm—George A. Grindahl

ABSTRACT

A curable organopolysiloxane composition comprising an organopolysiloxane gum having higher alkenyl groups, an organohydrogenpolysiloxane crosslinker, a solvent, a platinum group metal-containing catalyst and an inhibitor therefor provides for the formation of a tough, cured release film.

When this composition is coated on the surface of any of various types of substrates, for example, paper, synthetic resin films, fibers, etc., and then heated for 10 to 20 seconds at 80 to 90 degrees Centigrade, it forms a cured film which manifests an extremely stable release performance for tacky substances, such as, for example, pressure-sensitive adhesives, and the like, while at the same time evidencing an excellent adherence to the substrate itself.

The compositions can be used with synthetic resin films, such as polyolefin, which are easily deformed by heat and with poorly heat-tolerant paper.

9 Claims, No Drawings